

L27 ANSWER 1 OF 2 WPINDEX COPYRIGHT 2000 DERWENT INFORMATION LTD  
AN 1984-214301 [35] WPINDEX \*In German  
DNN N1984-160458 DNC C1984-090038

**TI Surface finishing or coating of cement-bound semi-finished goods - e.g. wood or fibre cement board using acid resin dispersion or acid soln. as primer.**

DC A82 G02 L01 P42 P63  
IN KOMARROW, E; ORTLEPP, W; PAA, K H  
PA (BAUS-N) BAUSCH V GMBH & CO; (ETER) ETERNIT AG  
CYC 1  
PI DE 3306780 A 19840823 (198435)\* 7p  
**DE 3306780** C 19860605 (198623)  
ADT DE 3306780 A DE 1983-3306780 19830223  
PRAI DE 1983-3306780 19830223  
AB DE 3306780 A UPAB: 19930925

In the surface treatment, esp. finishing and coating semifinished goods (I), such as wood- and/or fibre-cement boards, the cleaned and dried (I) are primed on all sides with an acid synthetic resin dispersion (II) and/or an aq. acid soln. (III) and, whilst still not completely dry, covered using acid-hardening dispersion adhesives (IV) or coated with acid-hardening dispersions (V).

Pref. (III) is an aq. acetic acid soln. with pH ca. 3, pref. contg. thickener and/or thixotropic agent.

USE/ADVANTAGES - Finishing, lamination and coating to give a decorative and even weather-resistant surface, e.g. for facade cladding boards, can be carried out. The use of (II) or (III) prevents inhibition of (IV) or (V) by the alkaline substrate.

0/0